

Knightsbridge

Easy Fitting Instructions



Helpful Advice Before Fitting

- These instructions are provided in an easy to follow style. Simply follow the instructions in sequence to fit this product.
- · Please retain all packaging until you have checked all the parts the parts list.
- To clean the surround we advise that you use a damp cloth and buff of with a soft, dry duster.
- · Please note: if fitting a gas fire a CORGI registered gas fitter must be used to install your gas fire
- These instructions are guide only, there are various other methods of fitting this fireplace.

In the unlikely event that this product has missing or damaged parts, please call our **help line on 0870 224 2811** or e-mail **helpline@adamsurrounds.co.uk** for assistance or to obtain spare parts.

Tool List:

- Pencil
- Measuring tape
- Silicone adhesive
- Cement (If fitting a Gas Fire)
- · Brackets for securing to the wall

Parts List:

Please ensure you have all the correct parts before beginning to fit this fire suite

- a) Hearth
- b) Legs left and right
- c) Cast iron back, optional 3 piece granite back panel, can be discarded if fitting cast iron back
- d) Front fascia
- e) Mantle
- f) Fret, ash pan cover and grate



Fitting the hearth and positioning the legs

Diagram A



Carefully unpack the hearth part A and position, ensure the hearth is centralised to your fireplace opening. if installing an electric fire, ensure you have sufficient room for the power cable of your electric fire to run to the socket

If having a gas fire installed ,prepare a bedding mixture, which can be sand and cement with an accelerator added to speed up hardening, or a special mixture available ready mixed. Lay the bedding mixture on the floor, ensuring sufficient depth of mixture to support the surround off the floor about 12mm and allow to harden.

Note: The hearth must be sealed directly on to bare floor so no air can enter the Flue from under the hearth. It must not be bedded directly on the carpet

Attach brackets (not supplied) onto each leg using a generous amount 2 part epoxy adhesive and allow to harden

Determine the position of the legs, which is central to both the hearth and the builders opening and mark off the position on the wall with a pencil and drill holes to attach the brackets and then fit wall plugs

Positioning the cast back panel

The back panel must have a air tight seal on to the wall

Slide the cast iron back panel and attached chair brick into the builders opening and cement into position.

Positioning the legs, fascia and mantel

Diagram B



Position legs to previously marked positions with both legs slightly off the wall apply silicone adhesive to the back of the legs and push the legs back on to the wall and fasten back with screws and brackets.

Position the fascia carefully on to the legs, ensuring the lipped edge sits on the legs. Secure in place with adhesive. Centralise the mantle on top of the fascia and secure in place with adhesive

Any gaps can be filled in with a good quality builder chalk

Attaching the grate, (optional for gas or solid fuel), fret and ash pan cover

If using solid fuel option secure grate in position by simply slotting into the hole on the back panel, see diagram B. Attach the fret by securing in the slots on the side of the cast back. Complete by sliding the ash pan cover into place

Diagram C



Installation Instructions for fitting a gas fire.

Note: It is a legal requirement that any installation of gas work is carried out by a CORGI Registered installer

This information provided within this instruction sheet is only a suggestion which can assist the installer to fit the fireplace correctly. There are other equally suitable methods of installing the fireplace

Please Note If you need any further advice or any spare parts for this item, please contact our customer service help line on 0870 224 2811 or e-mail helpline@adamsurrounds.co.uk for assistance.



Helpline telephone number: 0870 224 2811 Helpline email address: helpline@adamsurrounds.co.uk